

**SPECIFICATIONS:** TT-S-230C, Type II, Class A, ASTM C920 Type S, Grade NS, Class 50, Use T, M, G, A, O .

**APPLY TO:** Concrete, Brick, Block, Natural Stone, Porcelain & Ceramic Tile, Marble, Steel, Aluminum, Glass, Wood, Plastic, Vinyl and Fiberglass.

1. **DIRECTIONS:** WEAR IMPREVIOUS GLOVES – such as nitrile.
2. For best results store at 40°F (4 °C) to 75 °F (24 °C) for 24 hours prior to use.
3. The application are must be dry, sound, clean, frost free, and free of dirt, dust, loose debris, oils, greases, and any incompatible sealers/sealants that may prevent proper adhesion. For best results, maintain a width to depth ratio of 2 to 1. The minimum depth or placement is 1/4 in (6.3mm). If the joints depth exceeds 1/2 in (13 mm), use backer rod to maintain a joint depth that does not exceed 1/2 in (13 mm). For moving joints, use backer rod to prevent 3-point bonding. Always sand or abrade smooth surfaces to provide better bonding surface. Make sure to wear proper personal protection equipment when sanding or abrading.
4. Cut plastic tip to desired size and puncture airtight seal at base of tip. Using caulk gun, dispense sealant with the nozzle near the bottom of the joint to avoid trapping air during placement. Tool fresh sealant within 5-10 minutes of application.

**CURE TIME:** Product is moisture curing, allow exposure to air during curing process: 3-5 days for light use, full cure 14-28 days depending on temperature, humidity and thickness.

**LIMITATIONS:** Not intended for constant immersion. Apply to joints between 40 °F and 100 °F. Do not use for structural glazing. Sealant is custom color match, so slight color differences may appear. Please refer to the Product Data Sheet for complete instructions, uses, applications, safety, limitations & warranty information at [www.ezmixinc.com](http://www.ezmixinc.com).

**APPLICATION TEMP:** 40 °F (4 °C) to 100 °F (37.8 °C).

**WARNING: SKIN SENSITIZER; CAUSES SERIOUS EYE AND SKIN IRRITATION.** Use in a well ventilated area. May cause damage to lungs through prolonged or repeated inhalation. Harmful if swallowed. REMOVE PRODUCT WHILE WET: If washing does not remove, immediately use rubbing alcohol, carefully with no nearby flames. Once dry, this adhesive sealant can be removed only mechanically with difficulty. Wash contaminated skin and clothing after use. If in eyes; rinse cautiously with water for several minutes; remove contact lenses if easy to do; continue rinsing. If inhaled; remove person to fresh air and keep comfortable for breathing. If swallowed; rinse mouth; do NOT induce vomiting. Immediately seek medical attention if health symptoms are significant or persist. In case of an emergency call 1-800-535-5053.

KEEP OUT OF REACH OF CHILDREN



WARNING: Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



**E-Z MIX INC**

E-Z MIX INC. - 11450 Tuxford St. - Sun Valley, CA 91352  
P 818-768-0568 - [www.ezmixinc.com](http://www.ezmixinc.com)



## Adhesive Sealant

For Use in Expansion Joints for Masonry,  
Stone, Tile & Other Applications

- Exceptional Flexibility & Elongation
- Interior & Exterior Applications
- Superior UV Resistant
- Large Joints, up to 1"
- Commercial & Residential
- Mold & Mildew Resistant
- Easy to Use & Tool
- Available in Standard & Custom Colors



10.3 fl. Oz (310 ml)